

TurboVentura™ Natural Roof Ventilator

Refer to product table below for applicable product codes covered by this document

Issue **C**

Product Type & Application

The Bradford Ventilation TurboVentura™ is a wind driven natural ventilator that is designed to exhaust heat & moisture from the roof space, without the use of electrical energy. It is made of UV resistant engineering polymers with a 150mm throat.

Compliance with the NCC

For use in Australia, when correctly specified and installed, this product provides the following compliance;

NCC2022

- **Ventilation of Roof Spaces** - Meets the requirements of NCC2022 Volume 1 F8D5 and ABCB Housing Provisions Standard 2022 10.8.3 as a Deemed to Satisfy solution for condensation management for NCC Climate Zones 6, 7 and 8.
- **Weatherproofing** - Meets the requirements of the NCC 2022 Volume 2 Weatherproofing Performance Requirement H2P2 via Deemed-to-Satisfy (DtS) and performance solution pathways.

NCC2019

- **Ventilation of Roof Spaces** - Meets the requirements of the NCC2019 Volume 1 Amend.1 F6.4 and NCC 2019 Volume 2 Amend.1 3.8.7.4 as a Deemed-To-Satisfy solution.
- **Weatherproofing** - Meets the requirements of the NCC 2019 Volume 2 Amend. 1 Weatherproofing Performance Requirement P2.2.2 via Deemed-to-Satisfy (DtS) and performance solution pathways.

Evidence of Suitability

- Ventilation of roof spaces - Bradford Ventilation DTS Solution Calculation.
- Weatherproofing - Arcadis Report 30051677_4.

Conditions of Storage, Use & Maintenance

- Store in the original packaging in a cool and dry area.
- Do not attempt to repair – contact Bradford Ventilation for service advice.
- This product requires regular check for wear/tear.

Refer to the product warranty at bradfordventilation.com.au for more information.

Limitations of Use

- **IMPORTANT** - Do Not Modify This Product: Compliance with the evidence of suitability data referenced in this document is only achieved by the product or configuration listed in this PTS.
- This product has not been tested for use in cyclonic wind regions C or D.
- Do not use for exhausting hazardous, abrasive, acidic and alkaline vapour or areas containing explosive or corrosive materials.
- This product is not suitable for cyclonic rated regions.
- This product is not suitable for use in Bush Fire BAL-12.5 to BAL-40 or BAL-FZ rated areas.

Specific Design or Installation Instructions

- Isolate power before installation.
- This product requires specific areas to be sealed against water entry and other areas to be left unsealed to allow internal condensation drainage – refer to the installation guide for details.
- Assembly and installation must be accordance with the TurboVentura installation manual.
- Refer to the tables below for recommended ventilation levels. Note that there are differences in requirements between NCC 2019 and NCC 2022.
- The rotating head of this product must be installed horizontally to ensure correct operation.

For general installation guidance refer to the product installation guide at www.bradfordventilation.com.au

TurboVentura™ Natural Roof Ventilator

Specific Design or Installation Instructions cont.

NCC2022 Ventilation of Roof Spaces Deemed-To-Satisfy Solution Requirements Calculation in Table 1:

The table below indicates the ventilation opening requirements for condensation management in NCC Climate Zones 6, 7 and 8. The NCC gives an open area requirement per meter length of the longest horizontal dimension (e.g., the longest length of gutter) of the roof, the table indicates how many products are required based on this. Ventilation openings should be evenly distributed.

TurboVentura ventilators should be installed not more than 900mm below the ridge or highest point of the roof space, measured vertically.

Table 1. NCC 2022 Bradford Deemed-To-Satisfy Solution

Products	TurboVentura Roof Ventilator Requirement	Bradford Metal Eave Vent Requirement	Bradford Poly Eave Vent Requirement
Roof Pitch			
<10°		Install 1 Metal Eave Vent for every 0.7m of the longest horizontal roof length. These must be equally divided between the two opposing ends of the roof.	Install 1 Poly Eave Vent for every 0.4m of the longest horizontal roof length. These must be equally divided between the two opposing ends of the roof.
≥10° and <15°	1 TurboVentura for every 2.8m of the longest horizontal roof length.	1 Metal Eave Vent for every 1.4m of the longest horizontal roof length.	1 Poly Eave Vent for every 0.9m of the longest horizontal roof length.
≥15° and <75°	1 TurboVentura for every 2.8m of the longest horizontal roof length.	1 Metal Eave Vent for every 5.0m of the longest horizontal roof length.	1 Poly Eave Vent for every 3.3m of the longest horizontal roof length.
≥15° and <75° Cathedral	1 TurboVentura for every 2.8m of the longest horizontal roof length.	1 Metal Eave Vent for every 1.4m of the longest horizontal roof length.	1 Poly Eave Vent for every 0.9m of the longest horizontal roof length.

IMPORTANT APPLICATION NOTE: The number of vents required should be rounded up, not down, to ensure that the ventilation provided meets or exceeds the recommended requirement. For example, the ventilation requirement for a 10° pitched roof 20m long in the longest horizontal direction is calculated as follows:

- The ventilator requirement (1 per 2.8m) is calculated as follows: 20m divided by the recommended TurboVentura spacing of 2.8m = $20/2.8 = 7.1$ vents which should be rounded up to 8 TurboVenturas, to be evenly distributed along the roof.
- The metal eave vent requirement (1 per 1.4m) is calculated as follows: 20m divided by the recommended metal eave vent spacing of 1.4m = $20/1.4 = 14.2$ eave vents which should be rounded up to 16 metal eave vents, evenly distributed around the roof.

NCC2019 Ventilation of Roof Spaces Deemed-To-Satisfy Solution Requirements Calculation in Table 2:

The table below indicates the ventilation opening requirements for condensation management in all NCC Climate Zones when kitchen, bathroom, sanitary compartment or laundry exhaust systems are discharging into the roof space.

- Calculate the area (m²) of ceiling directly under the roof space;
- Determine the pitch of the roof;
- Look up the recommended number of TurboVentura and Bradford Metal Eave vents in the Deemed-To-Satisfy Solution Table below;
- Distribute the TurboVentura(s) and Bradford Metal Eave Vents evenly.

Table 2. NCC 2019 Bradford Deemed-To-Satisfy Solution

Roof Pitch	Total Ceiling Area ¹ (m ²)	Number of TurboVenturas required	Bradford Metal Eave Vents required	Bradford Poly Eave Vents required
> 22°	< 37	1	3	4
	< 75	2	6	8
	< 112	3	8	12
	< 150	4	11	15
	< 188	5	13	19
	< 225	6	16	23
≤ 22°	< 37	2	6	8
	< 75	4	12	16
	< 112	6	16	24
	< 150	8	22	30
	< 188	10	26	38
	< 225	12	32	46

Total Ceiling Area is defined as the total ceiling area directly under the roof/attic space.

Where the roof pitch is ≤ 22°, the number of ventilators and eave vents specified must be doubled for the same ceiling area.

TurboVentura™ Natural Roof Ventilator

Applicable Product Codes (SKU)

Colour	Material Code
Black	61375

Product Specifications

General	
Ventilator Type	Natural Roof Ventilator
Turbine Diameter	236 mm
Varipitch Diameter	154 mm
Throat Open Area	14320 mm ²
Product Weight	1.20 kg
Roof Pitch	Tiled Roofs 15° to 45° Metal Sheet Roofs 3° to 45° Note: Where applicable all roof pitches must comply to AS1562.1, the NCC & Australian Standards weatherproofing requirements within the ranges above.

Material	
Turbine	ASA Plastic
Varipitch	Aluminium
Flashing	Aluminium
Shaft	Aluminium
Rotation Bearings	Twin Ball Bearings

Product Dimensions (in mm)

